

Quick Guide Installation Steps

- 1 Important information before installation
- 2 Preconditions
- 3 Meter installation (Mechanical)
- 4 Enable radio / Configure meter for AMI
- 5 Configuration: Select AMI and frequency
- 6 Check meter readability

Important information before installation 1

Only installers are approved to perform installation

Further information on kamstrup.com

Further information on products.kamstrup.com

Preconditions 2.1

Download info to READY Manager from License Frequency Service

Kamstrup A/S
 Industrivej 28, Stilling
 DK-8660 Skanderborg
 T: +45 89 93 10 00
 F: +45 89 93 10 10
 info@kamstrup.com
 kamstrup.com

Preconditions 2.2

Synchronize READY Manager with READY App

Installation: External antenna 3.1

Insert the antenna into the sealing cap and turn the antenna 90°

Slide the antenna on the meter

Antenna is mounted

Installation: Meter placement 3.2

Correct meter placements in installation

Installation: Direction of flow 3.3

Correct direction

Wrong direction

Think forward

kamstrup



Kamstrup A/S - 55122185_AI_US_06.2018

4.1 Enable radio / Configure meter for AMI

Check display: If there is **FLOW**, the radio is **ON** ✓

If there is **NO FLOW** follow the next 5 steps →

4.2 Enable radio / Configure meter for AMI

Turn on all the devices

4.3 Enable radio / Configure meter for AMI

Pair devices with READY

The devices are paired ✓

4.4 Enable radio / Configure meter for AMI

Place optical eye on meter

4.5 Enable radio / Configure meter for AMI

4.6 Enable radio / Configure meter for AMI

Enter number

Enable radio

The icon "RadioOff" turns **OFF**. Radio is now **ENABLED** ✓

5.1 Configuration: Select AMI and frequency

AMI

Select **AMI** configuration file

MHz

Select **frequency**

5.2 Configuration: Select AMI and frequency

Keep short distance: Meter is configured for AMI ✓

6 Check meter readability

Meter is readable ✓

Wait up to 3 min.

www.kamstrup.com