

Quick Guide Installation Steps

- 1 Important information before installation
- 2 Preconditions
- 3 Meter installation (Mechanical)
- 4 Enable radio / Configure meter for AMI
- 5 Configuration: Select AMI and frequency
- 6 Check meter readability

Important information before installation 1

Only installers are approved to perform installation

Further information on kamstrup.com

Further information on products.kamstrup.com

Preconditions 2.1

Download info to READy Manager from License Frequency Service

Kamstrup A/S
 Industrivej 28, Stilling
 DK-8660 Skanderborg
 T: +45 89 93 10 00
 F: +45 89 93 10 10
 info@kamstrup.com
 kamstrup.com

Preconditions 2.2

Synchronize READy Manager with READy App

Installation: External antenna 3.1

Push the antenna into the meter

Push the sealing clasps into the meter

Antenna is mounted

Installation: Meter placement 3.2

Correct meter placements in installation

Installation: Direction of flow 3.3

Correct direction

Wrong direction

Think forward



Kamstrup A/S - 55122687_A1_US_07.2020

Enable radio / Configure meter for AMI 4.1

Check display: If there is **FLOW**, the radio is **ON** ✓

If there is **NO FLOW** follow the next 5 steps ▶

Enable radio / Configure meter for AMI 4.2

Turn on all the devices

Enable radio / Configure meter for AMI 4.3

Pair devices with READY

The devices are paired ✓

Enable radio / Configure meter for AMI 4.4

Place optical eye on meter

Enable radio / Configure meter for AMI 4.5

Enable radio / Configure meter for AMI 4.6

Enter number

Enable radio

The icon "RadioOff" turns **OFF**. Radio is now **ENABLED** ✓

Configuration: Select AMI and frequency 5.1

AMI

Select **AMI** configuration file

MHz

Select **frequency**

Configuration: Select AMI and frequency 5.2

Keep short distance: Meter is configured for AMI ✓

Check meter readability 6

Meter is readable ✓

Wait up to 3 min.

www.kamstrup.com